

THE ADVANTAGES OF THE MEGA DSS

Metric threads: M64 M100
UNC threads: UNC 2" 3/4-4 UNC 4"-4
Safety factor: 5 and 4
Machinery Directive 2006/42/CE
Norm EN 1677-1
Individual traceability number
Operating temperature: -20°C + 200°C
Swiveling under load (360° rotation and 180° swivel)

Your technical and quality advantages

Usable for any kind of lifting operation (straight lifts, with angle, turning, rotating)	absolute safety for any kind of lifting situation, no risk of wrong use
Optimized WLL/dimensions and weight ratio	wide shackle opening for installation of the hook, easy to use, high performance
Verification of each thread with calibrated gauge	no costs related to non-conformity, lifting rings can directly be put in use
Clear markings (CE, WLL, tightening torque)	reduction risk of incorrect use
Individual packaging and documents, delivery in sturdy packaging	quality and easy handling
Anti-tribocorrosion grease for life	easy rotation under load, built-in corrosion protection
Anti-corrosion coating (zinc coating) on bolt and base	limiting risk of corrosion in critical environments, durability of products

YOUR
OPTIONS

ALITRACER	effective follow-up (inspections, stock management ...)
------------------	---

Your service advantages

Short delivery times for standard products and specials guaranteed	no production breakdowns, operational gains, stock reduction
No minimum order quantity	stock reduction, quick fixes
Multilingual sales team	ease of communication, professional support
Fast on custom-made solution (case study and testing)	solution for special lifting applications
Experience of over 40 years	pledge of seriousness and professionalism
Free annual inspection at our factory	maintaining high safety level as annual check is conducted by the manufacturer
ISO and UNC as standard threads, special thread (optional)	one partner for your needs of swivel lifting rings
High quality material and marketing supports	videos, samples, technical drawings ...